

## Tandberg Data StorageLoader™ LTO

*Automate the manual swapping of backup tapes  
and significantly reduce the risk of data loss*

The Tandberg Data StorageLoader™ LTO offers the largest storage capacity, highest performance and best value of any product in its class. The StorageLoader LTO costs slightly more than a standalone tape drive, however by automating the swapping of daily backup tapes, it reduces the risk of data loss and saves you time and money.

The StorageLoader LTO offers scalable capacities up to 50TB\* and lightning fast performance up to 1.4 TB/hr\* in a compact 1U form factor. The StorageLoader LTO is available with either LTO-4, LTO-5 or LTO-6 tape drives and a choice of SCSI, SAS or FC connectivity.

The StorageLoader LTO contains two 4-slot removable magazines storing a total of 8 data cartridges. The StorageLoader LTO is easy to install, easy to use and is supplied with a barcode scanner, barcode labels and a rack-mount kit.

The StorageLoader LTO includes the latest security and data protection features, such as AES-256-bit Encryption and WORM (Write Once Read Many) to assist you with meeting today's data storage and archiving regulatory requirements.

The Web browser-based remote management interface allows you to monitor, control, configure and diagnose problems from anywhere in the world.

The StorageLoader LTO provides outstanding value for IT managers that require a easy to use, scalable, flexible, reliable and future-proof backup and data protection solution.



### Key Benefits

- ▬ **High Capacity in a Small Footprint**  
Up to 50TB\* storage capacity in a compact 1U form factor
- ▬ **High Performance**  
Transfer rates up to 1.4 TB/hr\*
- ▬ **Increased Security**  
AES 256-bit Encryption and WORM (Write Once Read Many)
- ▬ **Ease of Management**  
Browser-based remote management interface allows users to remotely monitor, control, configure and diagnose via the Internet
- ▬ **Minimise Downtime**  
Easy to install and easy to use



The Tandberg Data StorageLoader™ LTO combines high capacity and performance in an affordable 1U form factor.



TANDBERG DATA

## Specifications

	StorageLoader™ LTO-4	StorageLoader™ LTO-5	StorageLoader™ LTO-6
Capacity (native/compr.)	<b>6.4TB / 12.8TB*</b>	<b>12TB / 24TB*</b>	<b>20TB / 50TB*</b>
Performance (native/compr)	<b>288 GB/hr / 576 GB/hr*</b>	<b>0.5 GB/hr / 1.0 TB/hr*</b>	<b>0.6 GB/hr / 1.4 TB/hr*</b>
Interface	<b>SCSI LVD / SAS 3Gbs</b>	<b>SAS 6Gbs / FC 8Gbs</b>	<b>SAS 6Gbs</b>
External Connector	<b>68pin HD / SFF-8088</b>	<b>SFF-8088 / LC-Port</b>	<b>SFF-8088</b>
Drive Technology	<b>LTO-4 HH</b>	<b>LTO-5 HH</b>	<b>LTO-6 HH</b>
Read Compatibility	<b>LTO-2 / LTO-3 / LTO-4</b>	<b>LTO-3 / LTO-4 / LTO-5</b>	<b>LTO-4 / LTO-5 / LTO-6</b>
Write Compatibility	<b>LTO-3 / LTO-4</b>	<b>LTO-4 / LTO-5</b>	<b>LTO-5 / LTO-6</b>
Number of Cartridges	<b>8</b>	<b>8</b>	<b>8</b>
Number of Removable Magazines	<b>2</b>	<b>2</b>	<b>2</b>
Barcode Scanner	<b>Yes</b>	<b>Yes</b>	<b>Yes</b>
WORM (Write Once Read Many)	<b>Yes</b>	<b>Yes</b>	<b>Yes</b>
Encryption	<b>Yes</b>	<b>Yes</b>	<b>Yes</b>
MTBF	<b>250,000 hours</b>	<b>250,000 hours</b>	<b>250,000 hours</b>
Temperature (operating)	<b>10° – 35°C (50° – 95°F)</b>	<b>10° – 35°C (50° – 95°F)</b>	<b>10° – 35°C (50° – 95°F)</b>
Temperature (non-operating)	<b>-35° – 65°C (-31° – 148°F)</b>	<b>-35° – 65°C (-31° – 148°F)</b>	<b>-35° – 65°C (-31° – 148°F)</b>
Relative Humidity (operating)	<b>20 – 80%</b>	<b>20 – 80%</b>	<b>20 – 80%</b>
Relative Humidity (non-operating)	<b>10 – 90%</b>	<b>10 – 90%</b>	<b>10 – 90%</b>
Power Consumption	<b>100-240VAC, 50-60Hz, 35 W average</b>		
Certification Marks	<b>CE,UL,C-UL, GS / TUV, VCCI, C-Tick, UL-60950 / C-UL C22.2 No. 60950; TUV EN60950, FC Part 15, Class A; EN 55022, Class A; EN 61000-3-2, EN 61000-3-3, IEC60950, Class A; CISPR22, Class A, EN 55024</b>		
Web Administration	<b>System Status, Drive Operations, Remote Diagnostics, Remote Management</b>		
Language Support	<b>German, English, French, Italian, Spanish, Japanese</b>		
System Interface	<b>LC Display, Media Configuration and Diagnostic Status, Power and Alarm LED, 4-Button Keypad</b>		
Turnkey Solution	<b>Includes Barcode Reader and Labels, Rackmount Kit, Power Cable and Symantec Backup Exec QuickStart Edition</b>		

\* Assumes a compression ratio of 2:1 on LTO-4/5 & 2.5:1 on LTO-6.

<b>Form Factor</b>	<b>1U / 19" rack</b>
<b>Height</b>	<b>4.36cm / 1.72"</b>
<b>Width</b>	<b>44.66cm / 17.58"</b>
<b>Depth</b>	<b>73.66cm / 29.0" (behind the front rail)</b>
<b>Weight</b>	<b>14.6kg / 32.1lbs</b>

### About Tandberg Data

Tandberg Data is a wholly owned subsidiary of Overland Storage, Inc. and a leading global supplier of data protection solutions for small and medium-sized businesses. The company's wide range of cost-effective storage products and services provides customers with best-in-class tape, disk, removable disk and software solutions for backup, archiving and disaster recovery. These solutions are marketed through a global channel of qualified resellers, distributors and major server OEMs. An extensive service and support network supports all Tandberg Data products worldwide.

DS-SLLTO\_A4\_2014A

Overland Storage  
9112 Spectrum Center Blvd.  
San Diego, CA 92123  
USA

Tel: (858) 571-5555  
Fax: (585) 571-3664  
sales@overlandstorage.com  
www.overlandstorage.com

Tandberg Data U.S.  
10225 Westmoor Dr., Ste. 125  
Westminster, CO 80021  
USA

Tel: (800) 392-2983 Toll Free  
Fax: 303.417.7170  
sales@tandbergdata.com  
www.tandbergdata.com/us

Tandberg Data EMEA  
Feldstrasse 81  
44141 Dortmund  
Germany

Tel: 00 800 8263 2374 (00 800 TANDBERG)  
Fax: +49 (0) 231 5436 - 111  
salesemea@tandbergdata.com  
www.tandbergdata.com/emea

Tandberg Data APAC  
8 Cross Street, #28-00  
PWC Building  
Singapore 048424

Tel: (65) 6850 7820  
Fax: (65) 6850 7889  
salesapac@tandbergdata.com  
www.tandbergdata.com/apac